

# CHECK CHART

## COMMON SPECS FOR ALL POPULAR ENGINE MODELS

Model Series	Idle Speed	Armature Air Gap	Valve Clearance Intake	Valve Clearance Exhaust	Valve Guide Rejct Gage	Torque Specifications				Crankshaft Rejct Size			Crankshaft End Play	Main Bearing Rejct Gage Cr Rejct Dimension	Cylinder Bore Standard	NOTES
						Flywheel Nut Ft. Lbs.	Cylinder Head In. Lbs.	Conn. Rod Torque In. Lbs.	Crankcase Cover/ Sump In. Lbs.	Mag Journal	Crankpin Journal	PTO Journal				
<b>L-HEAD ALUMINUM/CAST SLEEVE SINGLE CYLINDER</b>																
80000	1750	.006 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	.870	.873	.002 .008	19166	2.374 2.375	
80000	1750	.006 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	.998	.873	.002 .008	19166	2.374 2.375	
90000	1750	.008 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	.896	.873	.002 .030	19166	2.5815 2.5825	* Horizontal Crankshaft - .002 - .010"
104000 thru 10M000	None	.005 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	.872	.873	.002 .030	19166	2.5615 2.5625	
110000	1750	.008 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	.996	.873	.002 .008	19166	2.7802 2.7812	
120000	1750	.006 .010	.005 .007	.007 .009	19122	55	140	100	90	.873	*.998 **1.097	1.060	.002 .030	19166 Mag. 19375 PTO	2.6875 2.6885	* Before 97011300 ** After 97011200
130000	1750	.010 .014	.005 .007	.009 .011	19122	55	140	100	120	.873	.996	.998	.002 .030	19166 Mag. 19178 PTO	2.5815 2.5825	* Horizontal Threaded Crankshaft - .002 - .008"
170000	1750	.010 .014	.005 .007	.009 .011	19151	65	165	165	140	.997	1.090	1.179	.002 .030	19178	2.639 3.000	* Horizontal Threaded Crankshaft - .002 - .008"
171700	1750	.010 .014	.005 .007	.009 .011	19151	65	165	165	140	1.179	1.122	1.179	.002 .030	19178	2.989 3.000	
190000	1750	.010 .014	.005 .007	.009 .011	19151	65	165	185	140	.997	1.122	1.179	.002 .030	19178	2.992 3.000	* Horizontal Threaded Crankshaft - .002 - .008"
191700	1750	.010 .014	.005 .007	.009 .011	19151	65	165	185	140	1.179	1.122	1.179	.002 .030	19178	2.989 3.000	
220000 250000	1750	.010 .014	.005 .007	.009 .011	19151	65	165	185	140	1.378	1.247	1.378	.002 .030	19219	3.4365 3.4375	
280000	1750	.010 .014	.005 .007	.009 .011	19151	85	185			1.378	1.247	1.378	.002 .023	19219	3.4365 3.4375	* Both Rod Screws Same Size: Torque to 185 In. Lbs. ** Torque Small Rod Screw First 180 In. Lbs. Torque Large Rod Screw Second 280 In. Lbs.
<b>L-HEAD CAST IRON SINGLE CYLINDER</b>																
230000	1200	.010 .014	.007 .009	.017 .019	19151	145	190	190	90 Mag 190 PTO	1.377	1.844	1.377	.002 .008	1.382	2.999 3.000	
240000	1200	.010 .014	.007 .009	.017 .019	19151	145	190	190	90 Mag 190 PTO	Ball	1.3094	Ball	.002 .008	Ball	3.0815 3.0825	
320000	1200	.010 .014	.007 .009	.017 .019	19151	145	190	190	90 Mag 190 PTO	Ball	1.3094	Ball	.002 .008	Ball	3.5815 3.5825	
<b>L-HEAD OPPOSED TWIN CYLINDER</b>																
400000 420000 480000	1400	.010 .014	.004 .006	.007 .009	19151	145	160	190	225	1.376	1.822	1.376	.002 .026	19219	3.4365 3.4375	* Clearance With Valve Springs Installed ** Horizontal Crankshaft - .004 - .012"
<b>OHV SINGLE CYLINDER</b>																
50000	1500	.012 .020	.004 .008	.004 .008	19382	55	250	90	90	Ball	.904	Ball	.002 .008	Ball	2.647 2.648	
85400	1300	.012 .020	.002 .004	.002 .004	19382	45	220	90	175	Ball	1.023	Ball	.001 .008	Ball	2.441 2.442	
87700 89700	1500	.006 .012	.005 .007	.005 .007	19122	60	160	100	85	.873	1.122	1.080	.002 .034	19166 Mag. 19178 PTO	2.5815 2.5825	
115400 117400 118400	1300	.012 .020	.002 .004	.002 .004	19382	45	220	90	175	Ball	1.1803	Ball	.001 .008	Ball	2.877 2.878	
120000 Horizontal Shaft	1750	.010 .014	.004 .006	.009 .011	19122	60	210	100	110	.878	1.097	1.065	.002 .033	19166 Mag. 19375 PTO	2.6875 2.6885	* Threaded Crankshaft - .002 - .008"
120000 Vertical Shaft	1750	.006 .014	.004 .006	.004 .006	19122	60	210	100	110	.878	1.087	.878	.002 .033	19166 Mag. 19375 PTO	2.6875 2.6885	
138400	1300	.012 .020	.002 .004	.002 .004	19382	45	220	90	190	Ball	1.1793	Ball	.001 .008	Ball	2.877 2.878	
185400	1300	.012 .020	.002 .004	.002 .004	19382	60	300	175	175	Ball	1.3368	Ball	.001 .008	Ball	3.1496 3.1504	
200000	1750	.008 .012	.004 .006	.004 .006	19381	100	220	100	200	1.178	1.2485	1.178	.002 .030	19380	3.119 3.120	* Threaded Crankshaft - .002 - .006"
210000 Horizontal Shaft	1750	.008 .012	.004 .006	.004 .006	19381	100	220	100	200	1.178	1.2465	1.178	.002 .030	19380	3.299 3.300	* Threaded Crankshaft - .002 - .008"
210000 Vertical Shaft	1750	.008 .012	.004 .006	.004 .006	19381	100	220	150	180	1.378	1.497	1.623	.002 .023	19219 Mag. 1.629" PTO	3.4365 3.4375	
235400 245400	1300	.008 .012	.004 .006	.004 .006	19382	60	35 Ft. lbs.	175	175	Ball	1.4953	Ball	.001 .008	Ball	3.1496 3.1504	
280000	1750	.010 .014	.003 .005	.005 .007	19381	100	220			1.378	1.247	1.378	.002 .023	19219	3.4365 3.4375	* Both Rod Screws Same Size: Torque to 185" Lbs. ** Torque Small Rod Screw First 180 In. Lbs. Torque Large Rod Screw Second 280 In. Lbs.
310000	1750	.010 .014	.003 .005	.005 .007	19381	100	220	150	180	1.378	1.497	1.378	.002 .023	19219	3.582 3.583	
<b>OHV TWIN CYLINDER</b>																
290000 294000 303000	**1100 **1400	.008 .012	.004 .006	.004 .006	19382	125	165	115	150	# 1.179 ## 1.376	1.455	1.375	.003 .015	# 19380 Mag. ## 19219 Mag. 19380 PTO	2.877 2.878	* White Governed Idle Spring ** Red Governed Idle Spring
350000	**1100 **1400	.008 .012	.004 .006	.004 .006	19382	125	165	115	150	# 1.179 ## 1.376	1.455	1.375	.003 .015	# 19380 Mag. ## 19219 Mag. 19380 PTO	2.835 2.836	* Before 97050100 ## After 97043000
380000	**1100 **1400	.008 .012	.004 .006	.004 .008	19382	125	165	115	150	# 1.179 ## 1.376	1.455	1.375	.003 .015	# 19380 Mag. ## 19219 Mag. 19380 PTO	2.9724 2.973	
405000	1750	.008 .012	.004 .006	.004 .006	19381	150	220	100	200	1.378	1.4965	1.623	.002 .030	19219 Mag. 1.629" PTO	2.989 2.970	
445000	1750	.008 .012	.004 .006	.004 .006	19381	150	220	100	200	1.378	1.4965	1.623	.002 .030	19219 Mag. 1.629" PTO	3.119 3.120	
540000	1500	.008 .012	.004 .006	.004 .006	19381	150	30 Ft. Lbs.	125	200	1.7895	1.8525	1.7895	.002 .012	1.777	3.3655 3.3665	




Fig. 1